

# LPQ 250

250 Watts

## LPQ 250 Series

Total Power	200 - 250 Watts
Input Voltages	85 - 264 VAC 120 - 370 VDC
# of Outputs	Quad



### SPECIAL FEATURES

- Active power factor correction
- IEC EN61000-3-2 compliance
- Remote sense on main output
- Power fail and remote inhibit
- Single wire current sharing
- Built-in EMI filter
- Adjustable isolated 4th output
- 2 Supervisory outputs 5 V and 12 V
- Overvoltage protection
- Overload protection
- Thermal overload protection
- DC power good
- Cover -C
- Optional with fan cover -CF
- Optional end fan cover -CEF

### ENVIRONMENTAL

Operating temperature: 0° to 50°C ambient derate each output at 2.5% per degree from 50° to 70°C

Electromagnetic susceptibility: Designed to meet IEC 801, -2, -3, -4, -5, -6, Level 3

Humidity: Operating; non-condensing 5% to 95%

Vibration: Three orthogonal axes, sweep at 1 oct/min, 5 min. dwell at four major resonances 0.7 G peak 5 Hz to 500 Hz, operational

Storage temperature: -40° to 85°C

Temperature coefficient: ±.04% per °C

MTBF demonstrated: >550,000 hours at full load and 25°C ambient conditions

### ELECTRICAL SPECIFICATIONS

#### Input

Input range	85-264 VAC; 120-370 VDC
Frequency	47-440 Hz
Inrush current	20 A max., cold start @ 25°C
Efficiency	75% typical at full load
EMI filter	FCC Class B conducted and radiated CISPR 22 Class B conducted and radiated EN55022 Class B conducted and radiated VDE 0878 PT3 Class B conducted and radiated.
Power factor	0.99 typical
Safety ground	
Leakage current	<0.5 mA @ 50/60 Hz, 264 VAC input

#### Output

Maximum power	With cover: 250 W with 30 CFM forced air, (-C) (-CF) (-CEF).
Adjustment range	±5% min. on main: 5-25 V on 4th output
Supervisory outputs	5 V @ 100 mA regulated, 12 V @ 500 mA
Hold-up time	20 ms @ 250 W load, 115 VAC nominal line
Overload protection	Short circuit protection on all outputs. Case overload protected @ 110-145% above peak rating
Overvoltage protection	5 V output: 5.7-6.7 VDC. Other outputs 10% to 25% above nominal output
Remote sense	Compensates for 0.5 V lead drop min. Will operate without remote sense connected. Reverse connection protected.

#### Logic Control

Power failure	TTL logic signal goes high 50-150 msec after 5V output. It goes low at least 4 msec before loss of regulation
Remote on/off	Requires an external contact (N.O or N.C) to inhibit outputs
DC OK	TTL logic goes high 50-150 msec after 5 V output. It goes low when there is loss of regulation.

### SAFETY

VDE	0805/EN60950 (IEC950)	11774-3336-1262
UL	UL1950	E132002
CSA	CSA 22.2-234 Level 5	LR53982C
NEMKO	EN 60950/EMKO-TUE (74-sec) 203	P95103550
BABT	EN60950/BS7002	605936
CB	Certificate and report	2186
CE	Mark (LVD)	

